## **Signal Warrant Study**

## City of Broadview Heights Cuyahoga County, Ohio

September 2010

Prepared by:

Northeast Ohio Areawide Coordinating Agency 1299 Superior Avenue Cleveland Ohio 44114-3204


JAMES R. GILLS, P.E., P.S. BOARD PRESIDENT

HOWARD R. MAIER, FAICP EXECUTIVE DIRECTOR

The preparation of this publication was financed through grants received from the Federal Highway Administration and the Ohio Department of Transportation and appropriations from the counties of and municipalities within Cuyahoga, Geauga, Lake, Lorain and Medina. The contents do not necessarily reflect official views or policies of the U.S. Department of Transportation or the Ohio Department of Transportation. This report does not constitute a standard or regulation.

The Northeast Ohio Areawide Coordinating Agency (NOACA) is a public organization serving the counties of and municipalities and townships within Cuyahoga, Geauga, Lake, Lorain and Medina (covering an area with 2.1 million people). NOACA is the agency designated or recognized to perform the following functions:

- Serve as the Metropolitan Planning Organization (MPO), with responsibility for comprehensive, cooperative and continuous planning for highways, public transit, and bikeways, as defined in the current transportation law.
- Perform continuous water quality, transportation-related air quality and other environmental planning functions.
- Administer the area clearinghouse function, which includes providing local government with the
  opportunity to review a wide variety of local or state applications for federal funds.
- Conduct transportation and environmental planning and related demographic, economic and land use research.
- Serve as an information center for transportation and environmental and related planning.
- At NOACA Governing Board direction, provide transportation and environmental planning assistance to the 172 units of local, general purpose government.



#### BOARD OFFICERS

President: Jam s R. Gills, P.E., P.S., Lake County Engineer First Vice-Pres dent: Peter Lawson Jones, President, Cuyahoga

County Board of Commissioners

Second Vice President: Stephen D. Hambley, Medina County

Commissioner

Secretary: Frank G. Jackson, Mayor, City of Cleveland

Assistant Secretary: Betty C. Blair, President, Lorain County Board

of Commissioners

Assistant Secretary: Robert C. Downey, City Manager, City of Cleveland Heights

Treasurer: Mary E. Samide, President, Geauga County Board of Commissioners

Assistant Treasurer: Julius Ciaccia, Jr., Executive Director,

Northeast Ohio Regional Sewer District

Assistant Treasurer: Robert E. Aufuldish, Lake County

Commissioner

Immediate Past President: William M. Grace, Mayor, City of Elyria

#### BOARD MEMBERS

#### **CUYAHOGA COUNTY**

Robert G. Blomquist, Mayor, City of Olmsted Falls

William R. Cervenik, Mayor, City of Euclid Joseph Cicero, Mayor, City of Lyndhurst Dean E. DePiero, Mayor, City of Parma Jimmy C. Dimora, Cuyahoga County Commissioner

Robert C. Downey, City Manager, Cleveland Heights

Edward O. FitzGerald, Mayor, City of Lakewood

Timothy Hagan, Cuyahoga County Commissioner

Peter Lawson Jones, President, Cuyahoga County Board of Commissioners

Robert C. Klaiber, Jr., P.E., P.S., Cuyahoga County Engineer

Earl M. Leiken, Mayor, City of Shaker Heights Michael S. Procuk, Mayor, Village of

Brooklyn Heights Leonard A. Spremulli, Mayor, City of

Bentleyville Robert A. Stefanik, Mayor, City of North Royalton

Deborah L. Sutherland, City of Bay Village

#### LORAIN COUNTY

Commissioners

CITY OF CLEVELAND

Frank G. Jackson, Mayor

GEAUGA COUNTY

of Commissioners

LAKE COUNTY

Martin Keane, Councilman

Mamie J. Mitchell, Councilman

Cleveland

Anthony Brancatelli, Councilman, City of

Jomarie Wasik, Director of Public Services

Tracy A. Jemison, Geauga County Commissioner

Mary E. Samide, President, Geauga County Board

William S. Young, Geauga County Commissioner

Robert E. Aufuldish, Lake County Commissioner

James R. Gills, P.E., P.S., Lake County Engineer

Raymond E. Sines, Lake County Commissioner

Daniel P. Troy, President, Lake County Board of

Mark A. Tyler, Mayor, City of Kirtland

Robert N. Brown, Director of Planning

Betty C. Blair, President, Lorain County Board of Commissioners

Kenneth P. Carney, Sr., P.E., P.S. Lorain County Engineer

G. David Gillock, Mayor, City of North Ridgeville

William M. Grace, Mayor, City of Elyria Ted Kalo, Lorain County Commissioner Anthony M. Krasienko, Mayor, City of Lorain Dale F. Rundle, Trustee, Columbia Township

Association

#### MEDINA COUNTY

J. Christopher Easton, Director of Public Services, City of Wadsworth

Stephen D. Hambley, Medina County Commissioner Michael J. Salay, P.E., P.S., Medina County Engineer Kathleen Scheutzow, Trustee, Brunswick Hills

NORTHEAST OHIO REGIONAL SEWER DISTRICT (NEORSD)

Julius Ciaccia, Jr., Executive Director

GREATER CLEVELAND REGIONAL TRANSIT AUTHORITY (GCRTA)

George M. Dixon, Board President

CLEVELAND-CUYAHOGA COUNTY PORT AUTHORITY: William Friedman, President/CEO

OHIO DEPARTMENT OF TRANSPORTATION (ODOT): Bonita G. Teeuwen, P.E., Deputy Director, **ODOT District 12** 

Ex officio Member: William T. Skowronski, Chief, Northeast District Office, Ohio Environmental Protection Agency (EPA)

#### ENVIRONMENTAL ADVISORY COMMITTEE

Chairperson: Mary E. Samide, Geauga County Commissioner

#### Air Quality Subcommittee Chair:

Robert E. Aufuldish, Lake County Commissioner

#### Water Quality Subcommittee Chair:

Dean E. DePiero, Mayor, City of Parma

#### **CUYAHOGA COUNTY**

Terry Allen, Cuyahoga County Health Commissioner

Anthony Brancatelli, Councilman, City of Cleveland

Matthew Carroll, Interim Director, Cleveland Public Health

Julius Ciaccia, Jr., Executive Director,

Jimmy C. Dimora, Cuyahoga County Commissioner

Ann Gliha, Environmental Services Manager, Cuyahoga County Sanitary Engineer's Office (representing Sanitary Engineers)

Mike Krzywicki, Cleveland Commissioner, Division of Air Quality

Jim Storer, Cuyahoga County Soil and Water Conservation District (representing Soil and Water Conservation Districts)

#### **GEAUGA COUNTY**

Mary E. Samide, Geauga County Commissioner

#### LAKE COUNTY

Robert E. Aufuldish, Lake County Commissioner James R. Gills, P.E., P.S., Lake County Engineer Nancy Niehus, Lake County Environmental Health (representing Local Air Agencies)

#### LORAIN COUNTY

Betty C. Blair, Lorain County Commissioner Ken Pearce, Lorain County Health Commissioner (representing Health Districts)

Kenneth P. Carney, Sr., P.E., P.S., Lorain County Engineer

#### MEDINA COUNTY

Stephen D. Hambley, Medina County Commissioner

#### NON VOTING MEMBERS:

Mark Durno, Acting Manager, Cleveland Office,

William T. Skowronski, Chief, Northeast District Office, Ohio EPA

#### PLANNING ADVISORY COMMITTEE

Chairperson: Robert N. Brown, Cleveland Planning Commission

Paul A. Alsenas, Director, Cuyahoga County Planning Commission

Jason Boyd, Director, Lake County Planning Commission

Robert N. Brown, Director, Cleveland Planning Commission David Dietrich, Director, Geauga County

Planning Commission

Patrice Theken, Director, Medina County Planning Commission (vacant) Director, Lorain County Planning Commission

#### TRANSPORTATION ADVISORY COMMITTEE

Chairperson: Robert C. Klaiber, Jr., P.E., P.S., Cuyahoga County Engineer

#### **CUYAHOGA COUNTY**

Paul A. Alsenas, Director, Cuyahoga County Planning Commission Thomas Boyer, Acting Commissioner, Cleveland Department of Engineering & Construction

Robert N. Brown, Director, Cleveland Planning Commission

Joseph A. Calabrese, General Manager, GCRTA Joseph Cicero, Mayor, City of Lyndhurst Jimmy C. Dimora, Cuyahoga County Commissioner

Robert C. Downey, City Manager, City of Cleveland Heights

Timothy F. Hagan, Cuyahoga County Commissioner

Martin J. Keane, Cleveland City Councilman Robert C. Klaiber, Jr., P.E., P.S., Cuyahoga County Engineer

Robert Mavec, Commissioner, Cleveland Traffic Engineering

#### **GEAUGA COUNTY**

David Dietrich, Director, Geauga County Planning Commission Robert L. Phillips, P.E., Geauga County Engineer Kristina Reider, Director, Geauga County Transit

Mary E. Samide, Geauga County Commissioner

#### LAKE COUNTY

Robert E. Aufuldish, Lake County Commissioner Jason Boyd, Director, Lake County Planning Commission

James R. Gills, P.E., P.S., Lake County Engineer Raymond Jurkowski, General Manager, Laketran Daniel P. Troy, Lake County Commissioner

#### LORAIN COUNTY

Betty C. Blair, Lorain County Commissioner Kenneth P. Carney, Sr., P.E., P.S., Lorain County Engineer

J. Christopher Easton, Director of Public Service, City of Wadsworth

Richard Enty, Interim General Manager, Lorain County Transit

Ted Kalo, Lorain County Commissioner (vacant) Director, Lorain County Planning Commission

#### MEDINA COUNTY

Stephen D. Hambley, Medina County Commissioner

Michael Salamone, Director, Medina County Transit

Michael J.Salay, P.E., P.S., Medina County Engineer

Patrice Theken, Director, Medina County Planning Commission

#### **OTHER VOTING MEMBERS: ODOT District** Deputy Directors:

Bonita G. Teeuwen, P.E., (ODOT 12)

John Hart (ODOT 3)

William T. Skowronski, Chief, Northeast District Office Ohio EPA

#### PRIVATE SECTOR VOTING MEMBERS:

Bethany Dentler, Executive Director, Medina County Economic Development Corporation (Medina County)

Frank Detillio, President, Lorain County Chamber of Commerce (Lorain County)

Deb Janik, Sr. Vice President, Greater Cleveland Partnership (Cuyahoga County)

John Loftus, Executive Director, Lake County Port Authority (Lake County)

Bill Skomrock, Jr., Safety Manager, DistTech Corp. (Geauga County)

#### NON VOTING MEMBERS:

James Cardina, Fairport Harbor Port Authority William Friedman, President/CEO, Cleveland Cuyahoga County Port Authority Ernest Gubry, Federal Aviation Administration Laurie Leffler, FHWA Ohio Division Administrator

Richard Novak, Executive Director, Lorain County Port Authority

Ricky D. Smith, Director, Cleveland Department of Port Control, Cleveland Hopkins International

Gary Suhadolnik, Executive Director, Ohio Turnpike Commission

#### **NOACA DIRECTORS**

Howard R. Maier, FAICP, Executive Director Stephen E. DeJohn, Esq., Director, Legal Counsel

Cheryl A. Kurkowski, CPA, Director of Finance & Operations

Planning and Programs Division Directors:

Ronald T. Eckner, P. E., Director of Planning John Hosek, Director of Programs

Planning and Programs Division Associate Directors:

Bill Davis, Associate Director of Planning Jonathan Giblin, Associate Director of Divisional Services

1)	Title & Subtitle:	2) Report No.:
	Signal Warrant Study	TR-10-09
	City of Broadview Heights	27
	Cuyahoga County, Ohio	5
3)	Author(s):	4) Report Date:
	Sahar Tawfiq, Transportation Engineer	September 2010
	Mahmoud Al-Lozi, Principal Planning Engineer	
	Contributors: Gayle L. Godek (Layout Design)	
5)	Performing Organization Name & Address:	6) Project & Task No. :
	New Alexand Old Association of the Control of the C	6251
	Northeast Ohio Areawide Coordinating Agency 1299 Superior Avenue, Cleveland, OH 44114-3204	
	Phone: (216) 241-2414 FAX: (216) 621-3024	7) Contract/Grant No.:
	Website: www.noaca.org	OD OT TWY
		ODOT/FHWA
8)	Sponsoring Agency Name & Address:	9) Type of Report & Period
		Covered:
	Ohio Department of Transportation	July 1, 2010 to June 30, 2011
	1980 W. Broad St., Box 899 Columbus, OH 43216-0899	
		10) Sponsoring Agency Code:
Fee	Supplementary Notes:  deral funding for this project was provided by the Federal Highway Administrate partment of Transportation. Twenty percent match is to be paid by the city of Brown and the city	
12)	Abstracts: This traffic signal warrant study was conducted as part of the Transpo program (TLC) for the city of Broadview Heights, Cuyahoga County. examined to evaluate the need for the installation of traffic signals at s	Signal warrants were
13	) Key Words & Document Analysis:	
	A. Descriptors: Traffic Control Signal Needs Studies	
	B. Identifiers/Open Ended Terms: Signal Warrants	
		15) No. Pages:
	A . W. L. W	
14	Availability Statement: Available in print and on the NOACA Website	16) Price:
	Available in print and on the NOACA Website	

## **Table of Contents**

Executive Summary
Background
Signal Warrant Analyses
Methodology
Analysis and Application
1: West Wallings Road and Briarwood Drive Intersection
2: East Royalton Road and Cherry Hill Lane/Ledgemont Drive Intersection9
3: Broadview Road and Akins Road/Faulhaber Road Intersection
4: Broadview Road and Valley Parkway Intersection
5: Broadview Road and Macintosh Lane/Hamilton Drive Intersection
6: Broadview Road and Boston Road Intersection22
Conclusion
Appendices:
Appendix A: Cuyahoga County Engineer's Office Traffic Count

Appendix B: Signal Warrants Analysis: Highway Capacity Software Outputs

### **Executive Summary**

hese signal warrant studies were conducted by the Northeast Ohio Areawide Coordinating Agency (NOACA) as part of the Transportation Links to Communities program (TLC) for the City of Broadview Heights in Cuyahoga County. Signal warrants were examined to evaluate the need for the placement of traffic signals at the following six intersections:

- 1. West Wallings Road and Briarwood Drive
- 2. East Royalton Road and Cherry Hill Lane/ Ledgemont Drive
- Broadview Road and Akins Road/ Faulhaber Road (City Hall Entrance)
- 4. Broadview Road and Valley Parkway Drive
- 5. Broadview Road and Macintosh Lane/ Hamilton Drive
- 6. Broadview Road and Boston Road


Traffic counts were collected by the Cuyahoga County Engineer's Office during the period of November through December 2009. NOACA used the signal warrant module of the most recent version of the Highway Capacity Software to analyze the data and perform the traffic signal warrants evaluation according to the guidelines and recommendations of the Ohio Manual of Uniform Traffic Control Devices (OMUTCD). Based on existing traffic volumes and existing roadway geometric conditions, traffic signals are not warranted at any of the studied intersections listed above.



### **Background**

he signal warrant analyses are part of a traffic engineering study conducted by the Northeast Ohio Areawide Coordinating Agency (NOACA) for the city of Broadview Heights in Cuyahoga County as part of NOACA's Transportation Links to Communities (TLC) program. The signal warrant study includes six intersections that are currently controlled by two-way stop signs. The analyses are for the intersections circled in Figure 1, which are from north to south:

- 1. West Wallings Road and Briarwood Drive
- 2. East Royalton Road and Cherry Hill Lane/ Ledgemont Drive
- 3. Broadview Road and Akins Road/ Faulhaber Road (City Hall Entrance)
- 4. Broadview Road and Valley Parkway Drive
- 5. Broadview Road and Macintosh Lane/ Hamilton Drive
- 6. Broadview Road and Boston Road



## **Signal Warrant Analyses**

#### Methodology

he traffic signal warrants analysis was performed according to the Ohio Manual of Uniform Traffic Control Devices (OMUTCD). A traffic signal is warranted if one or more of the following eight warrants are satisfied:

Warrant 1: Eight-Hour Vehicular Volume

Warrant 2: Four-Hour Vehicular Volume

Warrant 3: Peak Hour

Warrant 4: Pedestrian Volume

Warrant 5: School Crossing

Warrant 6: Coordinated Signal System

Warrant 7: Crash Experience
Warrant 8: Roadway Network

## Warrant 1: Eight-Hour Vehicular Volume

- Condition A: Applied at locations where a large volume of intersecting traffic is the principal reason to consider installing a traffic control signal.
- Condition B: Applied at locations where condition A is not satisfied and the minor road traffic experiences high delays and conflict in entering or crossing the major road.

For each of any eight hours of an average day the total volume in vehicles per hour (vph) of the major road and the higher volume (vph) of the two approaches of the minor road should exceed the minimum threshold traffic volumes defined in the OMUTCD. The thresholds are shown in the work sheet for each intersection. Where the posted speed limit exceeds 40 mph, or the intersection lies in a community of a population of less than 10,000 people, the traffic volumes thresholds are decreased to address such areas.

## Warrant 2: Four-Hour Vehicular Volume

This warrant is applied where the volume of intersecting traffic is the main reason to consider

installing a traffic control signal. The volume of at least four hours should exceed the minimum threshold outlined in the OMUTCD to justify this warrant. The thresholds are also decreased to address where the posted speed limit exceeds 40 mph, or the intersection lies in a community of a population of less than 10,000 people.

#### **Warrant 3: Peak Hour**

This warrant is applied where traffic conditions are such that for at least one hour the minor road traffic suffers undue delay. The point representing the vehicles per hour on the major street (total of both approaches) and the corresponding vehicles per hour on the higher-volume minor-street approach (one direction only) for one hour (any four consecutive 15-minute periods) of an average day falls above the applicable OMUTCD defined thresholds.

For warrants 1, 2 and 3, bicycles may be counted as vehicles when using the street with other vehicular traffic.

#### **Warrant 4: Pedestrian Volume**

The Pedestrian Volume signal warrant is intended for application where the traffic volume on a major street is so heavy that pedestrians experience excessive delay in crossing the major street. Bicyclists using pedestrian crossings may be counted as pedestrians.

The need for a traffic control signal at an intersection or midblock crossing would be considered if:

- Pedestrian volume crossing the major street during an average day is more than 100 for any four hours or 190 during any one hour, and
- The number of adequate gaps per hour in the traffic stream is less than 60 gaps during the same hours that the volume criterion is satisfied.

#### **Warrant 5: School Crossing**

The School Crossing signal warrant is intended for application where the principal reason to consider installing a traffic control signal is schoolchildren cross the major street.

The need for a traffic control signal would be considered if the number of adequate gaps in the vehicular traffic stream during the period when children are using an established school crossing is less than the number of minutes in the same period and there are a minimum of 20 students during the highest crossing hour.

## Warrant 6: Coordinated Signal System

A signal is warranted to maintain proper platooning through a coordinated signal system. A traffic control signal would be considered if the adjacent traffic control signals do not provide the necessary degree of platooning and the proposed and adjacent signal will collectively provide a progressive operation.

This warrant should not be applied where the resultant spacing of traffic control signals would be less than 1,000 feet.

#### **Warrant 7: Crash Experience**

The Crash Experience signal warrant conditions are intended for application where the severity and

frequency of crashes are the principal reasons to consider installing a traffic control signal.

A signal is warranted if following three criteria are met:

- **A.** Adequate trial of alternatives with satisfactory observance and enforcement has failed to reduce the crash frequency; and
- **B.** Five or more reported crashes, of types susceptible to correction by a traffic control signal, have occurred within a 12-month period.
- C. For each of any eight hours of an average day, the traffic volume (vph) given in both of the 80 percent columns of warrant 1 Condition A or Condition B must be met as defined in the OMUTCD.

#### **Warrant 8: Roadway Network**

A traffic control signal might be justified to encourage concentration and organization of traffic flow on a roadway network.

A traffic control signal would be considered if the common intersection of two or more major routes has an existing entering traffic volume and 5-year projected traffic volumes that would exceed the minimum threshold volumes defined by the OMUTCD.



## **Signal Warrant Analyses**

#### **Analysis and Application**

he analyses of Warrants 1, 2 and 3 are based on 24-hour traffic counts conducted by the Cuyahoga County Engineer's Office during the period of November 11 through December 4, 2009. Appendix A shows the traffic volumes and the seasonal adjustments used.

Warrants 4 and 5 are not applicable. None of the six intersections are close to a school or any pedestrian traffic generators. The distance to the nearest traffic controlled intersection on both sides of the intersections were taken into consideration for warrants 6 and 8.

The analysis of **Warrant** 7 is based on the Ohio Department of Public Safety (ODPS) data for the

years 2007-2009. The number and type of crashes susceptible to correction by a traffic signal was considered.

The signal warrant module of the Highway Capacity Software (HCS) was used to analyze the OMUTCD signal warrants.

The characteristics of each intersection and a summary table of the crashes for the three-year period (2007-2009) are described in the following sections. The signal warrant analysis for each intersection is summarized in a table at the end of each section.



#### 1. West Wallings Road and Briarwood Drive Intersection

#### **Existing Conditions**


- The intersection is three-legged and is located in a residential area. Figure 2 shows the layout of the intersection. The main roadway is Wallings Road, which consists of an 11-foot lane and two-foot paved shoulder in each direction. A five-foot sidewalk runs along the north side of Wallings Road. Briarwood Drive is a two-lane, two-way street with a total width of 21 feet. Pictures 1 and 2 show different views of the intersection.
- The posted speed limit on Wallings Road is 35 mph.
- The nearest signalized intersection along the main street are 0.83 mile east and 1.45 miles west of the intersection, respectively.
- The crashes at this intersection for the period 2007-2009 are summarized in the table below.

	Тур	e of Crash		Total
Year	Angle	Rear-End	Backing	Total
2007	-	1	-	1
2008	-	-	1	1
2009	-	1	-	1
Total	-	2	1	3

#### **Signal Warrants Evaluation**

 Based on the OMUTCD signal warrants and using the seasonally adjusted 24-hour traffic counts and the ODPS crash data, the intersection does not warrant a traffic signal. The analysis is summarized in Table 1. None of the eight signal warrants were satisfied by the traffic counts collected. The crash analyses show the occurrence of an average of one crash per year at the intersection. None of the reported crashes are of the type that can be avoided by installing a traffic control signal.







Picture 1: West Wallings Road and Briarwood Drive Intersection looking south



Picture 2: West Wallings Road and Briarwood Drive Intersection looking east

# SIGNAL WARRANTS EVALUATION

Intersection:	Intersection: Wallings Road and Briarwood Drive	nd Briarwood Driv	ve			And	Analysis By			NOACA						
Location :	Broadview Heights	ıts				F.	Traffic count date	date	: 11/1	11/11/2009		V		×	WARRANT #1 (Combination)	
Number of Lan	Number of Lanes per approach:	 Z	1 S=0	<b>=</b> 1	W= 1									Ŝ	Conditions A & B are each met at the 80% level:	
Does 70% warrant apply?		°Z									1	ZOACA	Y			
Major Street speed limit:		35 mph												M	WARRANT #4 (Pedestrian Volume)	
				$\vdash$				WARRANT #1	N #1			É	WARRANT	T	roou's with 190 or more pedestrians	
		Hourly	Hourly volumes			Condition A	4	$\vdash$		Condition B	8	#	#2 #3	Т	Pedestrian crossing time (†):	
Condition	No of Lanes	Major St. Minor St.	or St. Minor St.	r St.	100%	H	80%	H	100%		80%		⊢	T	Number of gaps greater than (†) during period:	
	10:01	2-way 1-	1-way 1-way		Major Min	Minor	Major	Minor A	Major	Minor	Major N	Minor	2000		Warrant Satisfied?	
Normal	1			D.							$\vdash$	800	пон	_		
	2+			9	-	200 4	$\exists$	160	006	100	720	80			WARRANT #5 (School Crossing)	
*%02	1			3	Н	Н			525	53	H	П			On approved school route?	
	2+			4	420 14	140 3	336	112	930	20	504	56	_	Gap	Gap analysis made during period from	
WID	MID to 1 AM	138	S	10										Ped	Pedestrian crossing time (†):	
1 AM	1 AM to 2 AM	79	4	_							0.		_	Z	Number of gaps greater than (†) during period:	
2 AM	2 AM to 3 AM	44	0											Z	Number of vehicles during analysis period:	- 29
3 AM	3 AM to 4 AM	15	2	-										App	Approximate vehicular speed:	
4 AM	4 AM to 5 AM	17	1	2		_								N N	Number of children crossing during period:	
5 AM	5 AM to 6 AM	25	2											W	Warrant Satisfied?	
6 AM	6 AM to 7 AM	129	9											Г		
7 AM	7 AM to 8 AM	437	16	9			×							WA	WARRANT #6 (COORDINATED SIGNAL SYSTEM)	
8 AM	8 AM to 9 AM	796	25		×		×		×		×			Dist	Distance to nearest signal in each direction on major street 0.83 mile East	st
9 AM	9 AM to 10 AM	748	35		×		×				×				1.45 mile West	sst
10 AM	10 AM to 11 AM	699	21		×		×				×			Ē	Time space diagram:	
11 AM 1	11 AM to 12 Noon	523	19	$\dashv$	×		×							Wai	Warrant Satisfied?	
12 Noo	12 Noon to 1 PM	618	12		×		×				×					
1 PM	1 PM to 2 PM	569	22	-	×		×							WA	WARRANT #7 (CRASH EXPERIENCE)	
2 PM	2 PM to 3 PM	609	19		×		×				×			Ade	Adequate trial of less restrictive measures:	
3 PM	3 PM to 4 PM	614	28	+	×		×				×			Z	Number of crashes per year which could be prevented by signalization: $\overline{0}$	
4 PM	4 PM to 5 PM	815	32	+	×		×		×		×			80%	80% of warrant #1 or #2 satisfied:	
5 PM	5 PM to 6 PM	923	32	-	×		×		×		×			Wil	Will signalization disrupt progressive movement?	
W 9	6 PM to 7 PM	1012	32	$\dashv$	×		×		×		×			Ν	Warrant Satisfied?	
7 PM	7 PM to 8 PM	913	41	+	×		×		×		×					
8 PM	8 PM to 9 PM	644	32	-	×		×				×			×	WARRANT #8 (ROADWAY NETWORK)	
9 PM 6	9 PM to 10 PM	442	23	3	+		×							Both	Both streets are considered major routes:	
10 PM	10 PM to 11 PM	347	21			-								¥	At least 1000 V.P.H. during weekday peak hour:	
11 PM	11 PM to MID	236	10	S	+	$\dashv$	+						-	5-Y	5-Year projection meets Warrant 1, 2, or 3:	
	Hour	Hours Met			0		0		0		0	0	0		At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:	
	WARRANT	WARRANT SATISFIED			No		No		N <sub>o</sub>		N	S	ο N		Meets Characteristic requirements?	
														Š	Warrant Satisfied?	
community with	* Condition is determined by environment; USe /US, values it the speed limit exceeds 40 MPH on the major road or if the location is in a build up area of an isolated community with a population of less than 10,000.	ss than 10,000.	7% values it i	the speed	IMIT exces	eds 40 mr	H on the r	najor roaa	or if the loc	ation is in c	build up are	a of an isolat	red	_		

Table 1: Warrant Analysis for the Intersection of West Wallings Road and Briarwood Drive

#### 2. East Royalton Road and Cherry Hill Lane/Ledgemont Drive Intersection

#### **Existing Conditions**


- The intersection is located in a residential area. Figure 3 shows the layout of the intersection. The main roadway is East Royalton Road (SR-82), which consists of a 12-foot lane in each direction and a 10-foot center two-way left-turn lane. The Ledgemont Drive approach consists of an exclusive 11-foot right-turn lane and a 12-foot shared through and left-turn lane. Cherry Hill Lane approach is a single 12-foot shared lane. Picture 3 shows the intersection east and west approaches.
- The nearest signal-controlled intersections east and west of the study intersection are East Royalton Road intersection with Avery Road and Broadview Road at a distance of 930 feet and 1,743 feet respectively.
- The posted speed limit on East Royalton Road is 35 mph.
- The crash data for the analysis period consisted of two angle crashes with severity of Property Damage Only (PDO).

	Тур	e of Crash	Tatal
Year	Angle	Rear-End	Total
2007	-	1	1
2008	-	-	-
2009	•	1	1
Total	-	2	2

#### **Signal Warrants Evaluation**

 Based on the OMUTCD signal warrants and using the seasonally adjusted 24-hour traffic counts and the ODPS crash data, the intersection does not warrant a traffic signal. The analysis is summarized in Table 2. None of the eight signal warrants were satisfied by the traffic counts collected. The crash analyses show the occurrence of an average of one crash per year at the intersection. None of the reported crashes are of the type that can be avoided by installing a traffic control signal.







Picture 3: East Royalton Road and Cherry Hill Lane/Ledgemont Drive Intersection looking west

# SIGNAL WARRANTS EVALUATION

									1	STOLAND MARKANIA CAMEOA TON		51.03			
Intersection: Royal	Ilton and Che	Royalton and Cherry Hill/ Ledgemont	dgemont				Analysis By	s By		NOACA			,		
Location : Broad	<b>Broadview Heights</b>	115					Traffi	Traffic count date		11/19/2009	6	VI.	W.		WARRANT #1 (Combination)
Number of Lanes per approach: Does 70% warrant apply?	roach	ž	2 "	<b>S</b> = 1	<b>п</b>	W= 1						N	ACA	_	Conditions A & B are each met at the 80% level:
Major Street speed limit:		35 mph													WARRANT #4 (Pedestrian Volume)
					L			3	WARRANT #1	77			WA	WARRANT	Hours with 190 or more pedestrians:
		ř	Hourly volumes	les		ြီ	Condition A				Condition B		#	#3	Pedestrian crossing time (1):
a sidifficant	130	Major St. Minor St.	Minor St.	Minor St.		100%	L	80%		100%	_	80%			Number of gaps greater than (t) during period:
	ol Laries	2-way	1-way	1-way	Major	Minor		r Minor	Major	Minor	Major	Minor	ЯN	Яľ	Warrant Satisfied?
Normal	1		NB NB		200	$\vdash$	H		750	75	009		ЮН	юн	SE VAN LICEUR AND
	5+			SB	009	-	-	160	006	100	720	80	AU	νĸ	WARRANT #5 (School Crossing)
*%02					350	$\dashv$	Н	$\dashv$	525	53	420	Н	03	,34	On approved school route?
80	5+				420	140	336	112	630	70	504	26			Gap analysis made during period from
MID to 1 AM	W	288	2	1											Pedestrian crossing time (†):
1 AM to 2 AM	W	165	3	0	500	_									Number of gaps greater than (t) during period:
2 AM to 3 AM	W	87	0	1											Number of vehicles during analysis period:
3 AM to 4 AM	W	78	0	0											Approximate vehicular speed:
4 AM to 5 AM	W	78	1	2											Number of children crossing during period:
5 AM to 6 AM	W	127	2	4											Warrant Satisfied?
6 AM to 7 AM	W	253	3	1											
7 AM to 8 AM	W	816	4	9	×		×		×		×				WARRANT #6 (COORDINATED SIGNAL SYSTEM)
8 AM to 9 AM	W	1391	25	18	×		×		×		×				Distance to nearest signal in each direction on major street:
9 AM to 10 AM	4W	1509	24	21	×		×		×		×				1743 ft. West
10 AM to 11 AM	4W	1296	14	33	×		×		×		×				Time space diagram :
11 AM to 12 Noon	loon	1179	11	14	×		×	W. C. M.	×		×				Warrant Satisfied?
12 Noon to 1 PM	PM	1234	14	24	×		×		×		×				
1 PM to 2 PM	¥	1338	15	22	×		×		×		×				WARRANT #7 (CRASH EXPERIENCE)
2 PM to 3 PM	¥	1310	13	23	×		×		×		×				Adequate trial of less restrictive measures:
3 PM to 4 PM	¥	1349	15	24	×		×		×		×				Number of crashes per year which could be prevented by signalization: 1
4 PM to 5 PM	¥	1527	32	56	×		×		×		×				80% of warrant #1 or #2 satisfied:
5 PM to 6 PM	¥	1615	22	33	×		×		×		×				Will signalization disrupt progressive movement?
6 PM to 7 PM	¥	1853	28	20	×		×		×		×			$\int$	Warrant Satisfied?
7 PM to 8 PM	×	1583	19	22	×		×		×		×				
8 PM to 9 PM	¥	1117	22	20	×		×		×		×				WARRANT #8 (ROADWAY NETWORK)
9 PM to 10 PM	W	903	2	10	×		×		×		×				Both streets are considered major routes:
10 PM to 11 PM	W	908	4	16	×		×		×		×				At least 1000 V.P.H. during weekday peak hour:
11 PM to MID	ı	497	1	9			×				_				5-Year projection meets Warrant 1, 2, or 3:
	Hours Met	s Met				0		0		0		0	0	0	At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:
	WARRANT	WARRANT SATISFIED				No		No		No		No	No	No	Meets Characteristic requirements?
* Condition is determined by environment: Use 70% values if the speed limit exceeds 40	nined by env	virnoment: U	Ise 70% va	lues if the	speed lin	nit excee	ds 40 MPF	fon the ma	or road or it	MPH on the major road or if the location is in a build up area of an isolated	is in a buil	d up area of	an isolate	טי	Warrant Satisfied?
community with a population of less than 10,000.	ulation of le	ss than 10,0													

Table 2: Warrant Analysis for the Intersection of Royalton Road and Cherry Hill Lane/Ledgemont Drive

#### 3. Broadview Road and Akins Road/Faulhaber Road Intersection

#### **Existing Conditions**

- The intersection is four-legged, with Faulhaber Road (City Hall Entrance) as the east leg of the intersection and Akins Road as the west leg, as illustrated in Figure 4. Broadview Road is a two-way, two-lane roadway of 24 feet total width with a three-foot paved shoulder on each side. The Akins Road approach is a single 10-foot shared lane with a two-foot paved shoulder on each side. The westbound approach is Faulhaber Road, which consists of a 10-foot left-turn bay and an 11-foot shared through and right-turn lane. Pictures 4 and 5 show the different approaches.
- There is a six-foot wide multipurpose path on the east side of Broadview road. The path widens to a 10-foot bicycle path (two-way) 250 feet south of the intersection and continues south to Valley Parkway Drive.
- The nearest signalized intersections are Oakes Road 500 feet north of Akins and Edgerton Road 0.8 mile south.
- The posted speed limit on both Broadview and Akins Roads is 35 mph.
- Seven intersection-related crashes were reported during the period 2007-2009: three angle crashes, three rear-end crashes and one bicycle-related.

	Тур	e of Crash		
Year	Angle	Rear-End	Bicycle- Related	Total
2007	2	· ·	1	3
2008	1	2	-	3
2009	-	1	-	1
Total	3	3	1	7

#### **Signal Warrants Evaluation**

- Based on the OMUTCD signal warrants and using the seasonally adjusted 24-hour traffic counts and the ODPS crash data, conditions at the intersection do not warrant a traffic signal. The analysis is summarized in Table 3. None of the eight warrants described in the OMUTCD to install a signal were met. A total of seven crashes were recorded in the three-year analysis
- period; three crashes were angle crashes that can be avoided by installing a signal but the threshold of five crashes per year was not met.
- Monitoring the change in the number of crashes and the change in traffic volumes to reevaluate this intersection in two years is recommended.







Picture 4: Broadview Road and Akins Road/Faulhaber Road Intersection looking east



Picture 5: Broadview Road and Akins Road/Faulhaber Road Intersection looking south

# SIGNAL WARRANTS EVALUATION

Intersection:	Broadview Road and Akins Road	and Akins Ro	bad			4	Analysis By		ź	: NOACA					
	<b>Broadview Heights</b>	ts t				-	Traffic cour	count date	: 12	12/4/2009		V		3	WARRANT #1 (Combination)
Number of Lanes per approach: Does 70% warrant apply?	s per approach: nt apply?	2	N=1 S= 1	= 1 <b>E</b> =2	W= 1							NGACA	CA	0	Conditions A & B are each met at the 80% level:
Major Street speed limit:		35 mph												<b>≯</b>   ĭ	WARRANT #4 (Pedestrian Volume) Hours with 100 or more pedestrians:
								WARR,	WARRANT #1		0		WARRANT	Γ	Hours with 190 or more pedestrians:
		ř	Hourly volumes	S		Condition A	on A	_		Condition B	n B		#5	#3	Pedestrian crossing time (t):
Condition	No of opes	+	Minor St.	Minor St.	100%	%(	80%		100%	ود	80%		H	Г	Number of gaps greater than (t) during period:
	vo. or cures	2-way	1-way	1-way				Minor	Major	Minor	Major	Minor	ЯN		Warrant Satisfied?
Normal	1		E8		200	150	400	120	750	75	009	09	юн	юн	
TO LOS	2+			WB	900	200	480	160	006	100	720	80	ЯN		WARRANT #5 (School Crossing)
*%UZ	1				350	105	280	84	525	53	420	42	FOI		On approved school route?
°°C	2+				420	140	336	112	630	70	504	99		Ğ	Gap analysis made during period from
MID to 1 AM	1 AM	166	8	0									H	<u>.</u>	Pedestrian crossing time (†):
1 AM to 2 AM	2 AM	26	9	0										Ž	Number of gaps greater than (t) during period:
2 AM to 3 AM	3 AM	33	4	0										Ž	Number of vehicles during analysis period:
3 AM to 4 AM	4 AM	29	11	3										₹	Approximate vehicular speed:
4 AM to 5 AM	5 AM	15	2	0										Ž	Number of children crossing during period:
5 AM to 6 AM	6 AM	33	11	0										≥	Warrant Satisfied?
6 AM to 7 AM	.7 AM	73	30	3											
7 AM to 8 AM	8 AM	248	65	17						×		×		3	WARRANT #6 (COORDINATED SIGNAL SYSTEM)
8 AM to 9 AM	9 AM	229	144	16	×		×	×		×	×	×		٥	Distance to nearest signal in each direction on major street: 500 ft. North
9 AM to 10 AM	10 AM	926	154	22	×	×	×	×	×	×	×	×	×		0.8 mile South
10 AM to 11 AM	11 AM	077	98	55	×		×		×	×	×	×		F	Time space diagram:
11 AM to 12 Noon	12 Noon	604	92	36	×		×			×	×	×		3	Warrant Satisfied?
12 Noon to 1 PM	to 1 P.M	693	79	86	×		×			×	×	×			
1 PM to 2 PM	2 PM	099	55	28	×		×				×			≩	WARRANT #7 (CRASH EXPERIENCE)
2 PM to 3 PM	3 P.M	640	89	33	×		×				×	×		¥	Adequate trial of less restrictive measures:
3 PM to 4 PM	4 PM	663	89	30	×	1	×	1			×	×	+	Ź	Number of crashes per year which could be prevented by signalization: 2
4 PM to 5 PM	5 P.W	865	110	95	×	+	× ;	+	× ;	×	× ;	× ;	+	<b>∞</b>	80% of warrant #1 or #2 satisfied:80% of warrant #1 or #2
MA DOT MA C	A DIE	076	3	7 2	< >		< >	+	< ,	< >	<b>,</b>	< >	,	<b>≥</b> ;	rupt progressive movement?
7 PM to 8 PM	W S	0411	89	63 84	×		< ×		< ×	<	< ×	< ×	<u> </u>	T	Warrant Satisfied.
8 PM to 9 PM	9 P.M	694	54	38	×		×				×			3	WARRANT #8 (ROADWAY NETWORK)
9 PM to 10 PM	10 PM	542	36	43	×		×							8	Both streets are considered major routes:
10 PM to 11 PM	, 11 PM	406	41	28			×							¥	At least 1000 V.P.H. during weekday peak hour:
11 PM to MID	o MID	284	22	11										ις	5-Year projection meets Warrant 1, 2, or 3:
	Hour	Hours Met			1		2		9		11		2	0	At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:
	WARRANT	WARRANT SATISFIED			No	0	No		No		Yes		No	No	Meets Characteristic requirements?
* Condition is de	Condition is determined by envirnoment: Use 70% values if the speed limit exceeds 40 MPH on the major road or if the location is in a build up area of an isolated	irnoment: U:	se 70% value	es if the spe	ed limit e	xceeds 40	MPH on the	major roa	d or if the	location is in	a build up	area of an isc	lated	}	Warrant Satisfied?
community with a population of less than 10,000.	population of le	ss than 10,00	9											╡	

Table 3: Warrant Analysis for the Intersection of Broadview Road and Akins Road

#### 4. Broadview Road and Valley Parkway Drive Intersection

#### **Existing Conditions**


- The intersection is located in a light density residential semi-rural area. Figure 5 and Pictures 6 through 8 show the layout of the intersection.
- The intersection is located on the crest of a vertical curve along Broadview Road.
- Flashing beacons are used in addition to the stop signs.
- A 10-foot wide bicycle path starts in the northeast quadrant of the intersection and extends north to Faulhaber Road (City Hall entrance).
- The main roadway is Broadview Road, which consists of a single 12-foot lane in each direction and four-foot paved shoulder on both sides of the roadway.

- Valley Parkway Drive eastbound and westbound approaches consist of a single 11foot shared lane.
- The nearest signal controlled intersections north and south of Valley Parkway Drive are 0.42 mile and 0.48 mile respectively.
- The posted speed limit on Broadview Road and Valley Parkway Drive are 45 mph and 30 mph, respectively.
- There were eight intersection related crashes at this location during the three-year period of 2007-2009. The crash severity of seven crashes was Property Damage Only and an Injury for the 2007 rear-end crash.

	Тур	e of Crash	7
Year	Angle	Rear-End	Total
2007	2	1	3
2008	1	2	3
2009	2	-	2
Total	5	3	8

#### **Signal Warrants Evaluation**

- Based on the OMUTCD signal warrants and using the seasonally adjusted 24-hour traffic counts and the ODPS crash data, conditions at the intersection do not warrant a traffic signal. The analysis is summarized in Table 4. None of the eight signal warrants described in the OMUTCD were met based on the existing traffic volumes counted at the intersection. A total of eight crashes were reported at the intersection in the three-year period (2007-
- 2009); three crashes were rear-end and five were angle crashes. The angle crashes could be prevented by installing a signal but their number does not meet the threshold of five crashes per year.
- Monitoring the change in the number of crashes and the change in traffic volumes to reevaluate this intersection in two years is recommended.





Picture 6: Broadview Road and Valley Parkway Drive Intersection looking north



Picture 7: Broadview Road and Valley Parkway Drive Intersection looking north



Picture 8: Broadview Road and Valley Parkway Drive Intersection looking east

# SIGNAL WARRANTS EVALUATION

	;	<b>3roadview Heigh</b>	115					Traffic c	ount date		#####					V
NAME	imber of Lane	s per approach			1 13								Z	AUA		t at the 80% level:
15 mph   1	es 70% warra		ž													
MARRANT #11	ajor Street sp		35 mph													WARRANT #4 (Pedestrian Volume)
MARRANT #1   MARRANT #1   MARRANT #2   #3   #3   #3   #3   #3   #3   #3																Hours with 100 or more pedestrians:
Manuer   Major   Maj			_	ulon Manot					WAR	ANT #1				WARR	TNA	Hours with 190 or more pedestrians:
Number of gaps greater than (t) during period:   Number of gaps greater than (t) dur				nonkiy volu	ımes		Cond	lition A			Condi	tion B		7#	#3	Pedestrian crossing time (t):
Main   Major   Minor   Major   Major   Minor   Major   Major		1 f.   mark	Major St	. Minor St		L	%00	8	%	100	%(	80	88			Number of gaps greater than (t) during period:
		Vo. or Lanes	2-way	1-way		Major	_	Major	Minor	Major	Minor	Major	Minor	Яſ	Яſ	
WARRANT #\$ (School Crossing)   20   20   20   20   20   20   20   2	-	1			H	200	150	400	120	750	75	009	09	юн	101	
280   84   525   53   420   42   20   20   20   20   20   2	Normal	2+				909	200	480	160	006	100	720	80	I AU	dK I	WARRANT #5 (School Crossing)
See paralysis made during period from   Pedestrian crossing time (†)	7004	1				350	105	280	84	525	53	420	42	FOI	/34	On approved school route?
Pedestrian crossing time (1)   Number of gaps greater than (1) during period.   Number of gaps greater than (1) during period.   Number of children crossing during period.   Number of crossing during period.   Number of crossing during period.   Number of crossing children crossing during period.   Number of crossing children crossing childr	100	2+				420	140	336	112	630	70	504	56			Gap analysis made during period from
Number of vehicles during period:   Number of vehicles special period:   Number of children crossing during period:   Number of crossing during period:   Number of crossing during progressive movement?   Number of crossing period:   Number of crossing period:   Number of crossing period:   Number of crossing progressive movement?   Number of crossing period:   Number of children period:   Number of chi	MID to	1 AM	82	80	1	L									Γ	Pedestrian crossing time (†):
Number of vehicles during analysis period:   Approximate vehicular speed:   Avaname of children crossing during period:   Avaname of children crossing during during during during children crossing during during children crossing during during during during during during during children crossing during	1 AM to	2 AM	55	4	1											Number of gaps greater than (t) during period:
Approximate vehicular speed:	2 AM to	3 AM	29	1	1											Number of vehicles during analysis period:
Number of children crossing during period:   X	3 AM to	4 AM	13	2	0											Approximate vehicular speed:
Warrant Satisfied?   Warrant Satisfied?     X	4 AM to	5 AM	23	1	2											Number of children crossing during period:
MARRANIT #6 (COORDINATED SIGNAL SYSTEM)	5 AM to	6 AM	56	9	1											
X         X	6 AM to	7 AM	129	10	1							Albert Co. Co.				
X         X         X         X           X         X         X         X           X         X         X         X           X         X         X         Y           X         X         X         X           X         X         X         X           X         X         X         X         X           X         X         X         X         X         X           X	7 AM to	8 AM	470	49	9			×								WARRANT #6 (COORDINATED SIGNAL SYSTEM)
X         X         X           X         X         X           X         X         X           X         X         Warrant Satisfied?           X         X         X           X         X         X         Adequate trial of less restrictive measures:           X         X         X         Adequate trial of less restrictive measures:           X         X         X         X         Adequate trial of less restrictive measures:           X         X         X         X         Adequate trial of less restrictive measures:           X         X         X         X         Adequate trial of less restrictive measures:           X         X         X         X         Adequate trial of less restrictive measures:           X         X         X         X         Warrant #I or #2 satisfied:           X         X         X         X         Warrant Satisfied?           X         X         X         X         X         X           X         X         X         X         X         X         X         X           X         X         X         X         X         X         X         X	8 AM to	9 AM	1130	109	00	×		×		×	×	×	×	×		Distance to nearest signal in each direction on major street:0.42 mile So
X         X         X           X         X         Warrant Satisfied?           X         X         Warrant Satisfied?           X         X         X           X	9 AM to	10 AM	1227	109	18	×		×		×	×	×	×	×		0.48 mile No
X         X         Warrant Satisfied?           X         X         X           X         X         Adequate trial of less restrictive measures:           X         X         X	10 AM 1c	, 11 AM	862	65	13	×		×		×		×	×			Time space diagram:
X         X         MARRANT #7 (CRASH EXPERIENCE)           X         X         Adequate trial of less restrictive measures:           X         X         X           X         X	11 AM to	12 Noon	684	42	16	×		×				×				Warrant Satisfied?NA
X         X         WARRANT #Z (CRASH EXPERIENCE)           X         X         Adequate trial of less restrictive measures:           X         X         X           X         X	12 Noon	to 1 P.M	734	38	28	×		×				×				
X         Adequate trial of less restrictive measures:           X         X <t< td=""><td>1 PM to</td><td>2 PM</td><td>753</td><td>36</td><td>28</td><td>×</td><td></td><td>×</td><td></td><td>×</td><td></td><td>×</td><td></td><td></td><td></td><td>WARRANT #7 (CRASH EXPERIENCE)</td></t<>	1 PM to	2 PM	753	36	28	×		×		×		×				WARRANT #7 (CRASH EXPERIENCE)
X         X         Number of crashes per year which could be prevented by signalized b	2 PM to	3 P.M	657	40	29	×		×				×				Adequate trial of less restrictive measures:
X         X	3 PM to	4 PM	929	49	28	×		×				×			2.000	Number of crashes per year which could be prevented by signaliza 2
X         X	4 PM tc	5 PM	716	92	40	×		×				×	×			
X         X	5 PM to	6 PM	847	54	28	×		×		×		×				Will signalization disrupt progressive movement?
X         X         X           X         X         WARRANT #8 (ROADWAY NETWORK)           X         Both streets are considered major routes:           Both streets are considered major routes:         At least 1000 V.P.H. during weekday peak hour:           At least 1000 V.P.H. during weekday peak hour:         At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:           No         No         No         No         Meets Characteristic requirements?           Marrant Satisfied?         Warrant Satisfied?	6 PM to	7 PM	920	64	47	×		×		×		×	×			
MARRANT #8 (ROADWAY NETWORK)	7 PM to	8 PM	809	41	23	×		×		×		×				
Both streets are considered major routes:	8 PM to	9 PM	484	30	15			×								WARRANT #8 (ROADWAY NETWORK)
At least 1000 V.P.H. during weekday peak hour   5 - Year projection meets Warrant 1, 2, or 3:   5 - Year projection meets Warrant 1, 2, or 3:   5 - 2 0   At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:   No	9 PM to	10 PM	309	18	11											Both streets are considered major routes:
5-Year projection meets Warrant 1, 2, or 3:::::::::::::::::::::::::::::::::::	10 PM +c	11 PM	249	24	8											At least 1000 V.P.H. during weekday peak hour:
No No No No No No No No No Meers Characteristic requirements?	11 PM t	, MID	146	9	3											5-Year projection meets Warrant 1, 2, or 3:
No No No No No Meets Characteristic requirements?  Warrant Satisfied?		Hour	's Met				0	٦		2		9		2	Г	At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:
MPH on the major road on if the location is in a build in area of an isolated		WARRANT	SATISFIEL				No	Z	0	ž	0	Ž	0	No		Meets Characteristic requirements?
	Condition is de	termined by en	virnoment	Use 70%	values if the	speed lin	it exceeds		n the majo	road or if	the locativ	on is in a bu	ild up area	of an isola		Warrant Satisfied?

Table 4: Warrant Analysis for the Intersection of Broadview Road and Valley Parkway Drive

#### 5. Broadview Road and Macintosh Lane/Hamilton Drive Intersection

#### **Existing Conditions**

- The intersection is located in a residential area.
   Figure 6 and Picture 9 show the layout of the intersection.
- The main roadway is Broadview Road, which consists of a single 12-foot lane in each direction and 4.5-foot paved shoulder on each side.
- Macintosh Lane and Hamilton Drive approaches are a single shared lane 16-foot and 24-foot wide, respectively.
- The nearest signal controlled intersections are at Edgerton Road 0.84 mile north of Macintosh Lane and at SR-303(Center Road) 3.3 miles south.
- The posted speed limit on Broadview Road is 45 mph.
- There were five intersection related crashes at this location during the analysis period; all crash severities were PDO except the 2007 rear-end crash was an injury.

	Тур	e of Crash	Total
Year	Angle	Rear-End	Total
2007	1	1	2
2008	-	2	2
2009	1		1
Total	2	3	5

#### **Signal Warrants Evaluation**

- Based on the OMUTCD signal warrants and using the seasonally adjusted 24-hour traffic counts and the ODPS crash data, the intersection does not warrant a traffic signal. The analysis is summarized in Table 5. None of the eight signal warrants described in the OMUTCD were met based on the existing
- traffic volumes counted at the intersection and crash data. The reported number of crashes that can be prevented by installing a signal reported is two angle crashes for the three-year analysis period, which does not meet the threshold of five crashes per year.




Figure 6: The Intersection of Broadview Road & Macintosh Lane/Hamilton Drive



Picture 9: Broadview Road and Macintosh Lane/Hamilton Drive Intersection looking north

# SIGNAL WARRANTS EVALUATION

Intersection: Broadview	Broadview Road and Macintosh Lane/Hamilton Driv	itosh Lane/	'Hamilton D	ć		Analysis By	By		NOACA				7	
Location : Broadview Heights	Heights					Traffic	Traffic count date		11/17 and 12/03/2009	/03/2009				WARRANT #1 (Combination)
Number of Lanes per approach:	roach:	ž	<b>S</b> = 1	E=1	Ä							NOTACA		Conditions A & B are each met at the 80% level:
Major Street speed limit:														WARRANT #4 (Pedestrian Volume)
														Hours with 100 or more pedestrians:
16.7		Mounty volumes		Ц			W	WARRANT #1				WAR	WARRANT	Hours with 190 or more pedestrians:
		and di more	3		ŭ	Condition A			Condit	Condition B		#2	#3	Pedestrian crossing time (†):
Condition No of lones		t. Minor St	Major St. Minor St. Minor St.		100%		80%	10	100%	80	80%			Number of gaps greater than (t) during period:
	2-way	1-way	1-way	_	or Minor	_	Minor	Major	Minor	Major	Minor	ЯN	Яſ	Warrant Satisfied?
1				200	0 150		120	750	75	009	09	ЮН	101	
2+				900	0 200	_	160	006	100	720	80	an	dK i	WARRANT #5 (School Crossing)
70%*				350	0 105	280	84	525	53	420	42	POI	/3d	On approved school route?
2+				450	0 140	336	112	630	70	504	56			Gap analysis made during period from
MID to 1 AM	98	3	s	L										Pedestrian crossing time (†):
1 AM to 2 AM	95	1	Е											Number of gaps greater than (t) during period:
2 AM to 3 AM	23	2	0											Number of vehicles during analysis period:
3 AM to 4 AM	00	0	-											Approximate vehicular speed:
4 AM to 5 AM	16	0	1											Number of children crossing during period:
5 AM to 6 AM	9	2	2											Warrant Satisfied?
6 AM to 7 AM	25	00	11											
7 AM to 8 AM	134	16	39											WARRANT #6 (COORDINATED SIGNAL SYSTEM)
8 AM to 9 AM	364	20	134	×	×	×	×		×		×			Distance to nearest signal in each direction on major street:
9 AM to 10 AM	425	97	172	×	×	×	×		×	×	×			
10 AM to 11 AM	336	64	123		×	×	×		×		×			Time space diagram:
11 AM to 12 Noon	299	45	72			×			×		×			Warrant Satisfied?
12 Noon to 1 PM	324	28	53			×			×		×			
1 PM to 2 PM	361	36	47	×		×					×			WARRANT #7 (CRASH EXPERIENCE)
2 PM to 3 PM	370	40	20	×		×					×			Adequate trial of less restrictive measures:
3 PM to 4 PM	384	56	35	×		×								nted by s
4 PM to 5 PM	475	43	99	×		×			×	X	×			80% of warrant #1 or #2 satisfied:
5 PM to 6 PM	576	39	29	×		×		×	×	×	×			Will signalization disrupt progressive movement?
6 PM to 7 PM	658	30	99	×		×		×	×	×	×			Warrant Satisfied?
7 PM to 8 PM	569	39	82	×		×		×	×	×	×			
8 PM to 9 PM	366	27	87	×		×	×		×		×	0.00		WARRANT #8 (ROADWAY NETWORK)
9 PM to 10 PM	259	14	41											Both streets are considered major routes:
10 PM to 11 PM	211	6	40											At least 1000 V.P.H. during weekday peak hour:
11 PM to MID	114	9	2											5-Year projection meets Warrant 1, 2, or 3:
	Hours Met				2		4		3	47	5	0	0	At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:
WAR	WARRANT SATISFIED				No		No	2	No	Z	No No	å	<sub>S</sub>	Meets Characteristic requirements?
* Condition is determined by envirnoment: Use 70% values if the speed limit exceeds 40 MPH on the major road or if the location is in a build up area of an isolated community	by envirnoment:	. Use 70% v	values if the	speed	limit excee	ds 40 MPH	on the majo	r road or if	the location	blind a hild	up area of a	n isolated co	ommunity	Warrant Satisfied?NA
with a population of less than 10,000.	an 10,000.						•							
	-												ĺ	

Table 5: Warrant Analysis for the Intersection of Broadview Road and Macintosh Lane/Hamilton Drive

#### 6. Broadview Road and Boston Road Intersection

#### **Existing Conditions**


- The intersection is located in a light density residential semi-rural area. Figure 7 and Pictures 10 through 12 show the intersection layout.
- The main roadway is Broadview Road, which consists of a single 12-foot lane in each direction and five-foot shoulder on both sides of the roadway.
- Boston Road is a two-way two-lane roadway.
   The lanes are 11-foot wide east of Broadview
   Road and 10-foot wide west of it.

- The nearest signal controlled intersections north and south of Boston Road are 1.1 miles and 3.0 miles respectively.
- The posted speed limit on Broadview Road is 45 mph.
- There were 13 reported crashes at this location during the three-year period of 2007-2009.
   The severity of five of the angle crashes was injury.

	Туре		
Year	Angle	Animal	Total
2007	1	-	1
2008	3	2	5
2009	6	1	7
Total	10	3	13

#### **Signal Warrants Evaluation**

- Based on the OMUTCD signal warrants and using the seasonally adjusted 24-hour traffic counts and the ODPS crash data, the intersection does not warrant a traffic signal. The analysis is summarized in Table 6. The number of crashes during 2009 that are susceptible to correction by traffic signal is more than five but the traffic volumes do not satisfy the third criteria of Warrant 7.
- Alternatives to reduce the number of crashes should be considered such as improving warning signs and using flashing beacons for all approaches.
- Monitoring the change in the number of crashes and the change in traffic volumes to reevaluate this intersection in two years is recommended.





Picture 10: Broadview Road and Boston Road Intersection looking west



Picture 11: Broadview Road and Boston Road Intersection looking east



Picture 12: Broadview Road and Boston Road Intersection looking south

Z
ō
н
4
3
$\supset$
A
₽
S
5
₹
œ
4
š
_
₹
SIGN
SI

. coation :	<b>Broadview Heights</b>	thts												
mhen of 10	Nimber of Loner nen opproach:	4	N-1				Traffic count date	ount date	: 12,	: 12/2/2009				
mber of LC es 70% war	Number of Lanes per approact Does 70% warrant apply?	cn: Yes	Ž	ر ا = ا	<u>ا</u>	<b>W</b> = 1						NON	ACA	Conditions A & B are each met at the 80% level:
jor Street	Major Street speed limit:	45 mph		23										WARRANT #4 (Pedestrian Volume) Hours with 100 or more pedestrians:
		i	House of the second					WAR	WARRANT #1				WARRANT	Hours with 190 or more pedestrians:
			in the second	3		Condi	Condition A			Condition B	9.	#5	#	Pedestrian crossing time (1):
Condition	No. of Lanes	Major St.	Major St. Minor St. Minor St.	Minor St.	10		80%		100%	П	80%			an (t) during period:
		2-way	1-way	1-way	Major						<	I	AU	Warrant Satisfied?
Normal	(				200	150	400	120	+	+	-	ОН	он	
	+7			-	9009	000	480	160	+	+	+	Т	:VK	WARRANT #5 (School Crossing)
*%02	1				350	105	280	84	525				34	On approved school route?
	5+				420	140	336	112	630	70	504 56	9		Gap analysis made during period from
WID	MID to 1 AM	47	1	10										Pedestrian crossing time (†):
1 AM	1 AM to 2 AM	27	2	2										Number of gaps greater than (t) during period:
2 AM	2 AM to 3 AM	13	1	2										Number of vehicles during analysis period:
3 AM	3 AM to 4 AM	5	0	1										Approximate vehicular speed:
4 AM	4 AM to 5 AM	14	8	0										Number of children crossing during period:
5 AM	5 AM to 6 AM	9	4	3										Warrant Satisfied?
6 AM	6 AM to 7 AM	32	14	11										
7 AM	7 AM to 8 AM	134	62	\$2						×	×			WARRANT #6 (COORDINATED SIGNAL SYSTEM)
8 AM	8 AM to 9 AM	354	120	88	×	×	×	×		×	×			Distance to nearest signal in each direction on major street:
9 AM	9 AM to 10 AM	355	136	29	×	×	×	×		×	×			
10 AM	10 AM to 11 AM	268	89	39						×	×			Time space diagram:
11 AM T	11 AM to 12 Noon	233	33	47							×			Warrant Satisfied?
12 Noo	12 Noon to 1 PM	265	30	51							×			
1 PM	1 PM to 2 PM	268	37	37										WARRANT #7 (CRASH EXPERIENCE)
2 PM	2 PM to 3 PM	261	41	52							×	_		Adequate trial of less restrictive measures:
3 PM	3 PM to 4 PM	330	25	09			×			×	×			Number of crashes per year which could be prevented by signalization: 6
4 PM	4 PM to 5 PM	364	47	77	×		×			×	×			80% of warrant #1 or #2 satisfied:
5 PM	5 PM to 6 PM	448	05	125	×	×	×	×		×	×			lent?
6 PM	6 PM to 7 PM	516	88	144	×	×	×	×		×	×			Warrant Satisfied?
7 PM	7 PM to 8 PM	402	51	78	×		×			×	×			
8 PM	8 PM to 9 PM	260	41	29										WARRANT #8 (ROADWAY NETWORK)
9 PM 1	9 PM to 10 PM	189	28	24										Both streets are considered major routes:
10 PM	10 PM to 11 PM	153	13	19										At least 1000 V.P.H. during weekday peak hour:
11 PM	11 PM to MID	86	11	17										5-Year projection meets Warrant 1, 2, or 3:
	Hon	Hours Met			,	4	4		0	$\vdash$	2	0	0	At least 1000 V.P.H. for any 5 hours on a Saturday or Sunday:
	WARRAN	WARRANT SATISFIED			Z	No	N <sub>o</sub>		Š		N <sub>o</sub>	S.	Š	Meets Characteristic requirements?
				-		1				1			1	

Table 6: Warrant Analysis for the Intersection of Broadview Road and Boston Road

#### Conclusion

ased on the Ohio Manual of Uniform
Traffic Control Devices (OMUTCD) traffic signal warrants evaluation methodology, the existing geometric and traffic conditions at the six intersections do not justify the installation of traffic signals. The analyses are based on the Cuyahoga County Engineer's Office traffic counts for the period November through December 2009 and the Ohio Department of Public Safety (ODPS) crash data for the years 2007-2009.

Monitoring the change in number of crashes and the increase in traffic volumes are recommended to reevaluate the signal warrants in two years for the following locations:

- Broadview Road and Akins Intersection
- Broadview Road and Valley Parkway Drive Intersection
- Broadview Road and Boston Road Intersection

Consider alternatives to reduce the number and severity of crashes, such as improving warning signs and using flashing beacons at all approaches and/or transverse lane markings on Broadview Road to alert drivers approaching the intersection, for the following locations:

- Broadview Road and Boston Road Intersection
- Broadview Road and Macintosh Lane/ Hamilton Drive Intersection

## **Appendices**

A: Cuyahoga County Engineer's Office Traffic Count

B: Signal Warrants Analysis: Highway Capacity Software Outputs

## Appendix A: Cuyahoga County Engineer's Office Traffic Count

### **West Wallings Road and Briarwood Drive Intersection**

Tro	ffic Volun	ne Summa	ıry (11/11/20	009) Adjusted Volum				
Time	EB	WB	EB+WB	SB	EB+WB	SB		
0:00	39	95	134	5	138	5		
1:00	17	60	77	4	79	4		
2:00	12	31	43	0	44	0		
3:00	6	9	15	2	15	2		
4:00	11	6	1 <i>7</i>	1	17	1		
5:00	15	9	24	2	25	2		
6:00	103	22	125	6	129	6		
7:00	362	63	425	16	437	16		
8:00	639	135	774	24	796	25		
9:00	521	206	727	34	748	35		
10:00	412	238	650	20	669	21		
11:00	267	241	508	18	523	19		
12:00	299	302	601	12	618	12		
13:00	242	311	553	21	569	22		
14:00	305	287	592	18	609	19		
15:00	272	325	597	27	614	28		
16:00	280	512	792	31	815	32		
17:00	310	587	897	31	923	32		
18:00	321	662	983	31	1012	32		
19:00	330	557	887	40	913	41		
20:00	268	358	626	31	644	32		
21:00	146	284	430	22	442	23		
22:00	100	237	337	20	347	21		
23:00	76	153	229	10	236	10		
	5,353	5,690		426		438		

Seasonal Adjustment Factor = 1.029

## Appendix A: Cuyahoga County Engineer's Office Traffic Count

## East Royalton Road & Cherry Hill Lane/Ledgemont Drive Intersection

	Traffic Volume Summary (11/19/2009)									mes
Time	EB	EBLT	WB	WBLT	EB+WB	NB	SB	EB+WB	NB	SB
0:00	97	0	176	3	276	2	1	288	2	1
1:00	57	1	97	3	158	3	0	165	3	0
2:00	29	2	49	3	83	0	1	87	0	1
3:00	34	1	40	0	75	0	0	78	0	0
4:00	40	0	34	1	75	1	2	78	1	2
5:00	74	0	48	0	122	2	4	127	2	4
6:00	181	0	61	0	242	3	1	253	3	1
7:00	631	1	147	3	782	4	6	816	4	6
8:00	954	1	371	6	1332	24	17	1391	25	18
9:00	945	6	488	6	1445	23	20	1509	24	21
10:00	758	4	472	7	1241	13	32	1296	14	33
11:00	642	6	477	4	1129	11	13	1179	11	14
12:00	585	8	582	7	1182	13	23	1234	14	24
13:00	586	5	688	3	1282	14	21	1338	15	22
14:00	618	5	627	5	1255	12	22	1310	13	23
15:00	628	9	645	10	1292	14	23	1349	15	24
16:00	619	11	829	4	1463	31	25	1527	32	26
17:00	610	12	920	5	1547	21	32	1615	22	33
18:00	675	7	1090	3	1775	27	19	1853	28	20
19:00	547	18	948	3	1516	18	26	1583	19	27
20:00	436	11	617	6	1070	21	48	1117	22	50
21:00	325	8	528	4	865	5	10	903	5	10
22:00	269	8	489	6	772	4	15	806	4	16
23:00	190	4	281	1	476	1	6	497	1	6
	10,530	128	10,704	93		267	367			

Seasonal Adjustment Factor = 1.044

## Appendix A: Cuyahoga County Engineer's Office Traffic Count

## **Broadview Road and Akins Road/Faulhaber Road Intersection**

Traffic Volume Summary (12/04/2009)							Ad	justed V	olumes
Time	EB	WB	EB+WB	NB	SB	NB+SB	EB	WB	NB+SB
0:00	7	0		46	108	154	8	0	166
1:00	6	0		29	56	85	6	0	92
2:00	4	0		11	20	31	4	0	33
3:00	10	3		10	17	27	11	3	29
4:00	5	0		6	8	14	5	0	15
5:00	10	0		16	15	31	11	0	33
6:00	28	3		42	26	68	30	3	73
7:00	90	16		159	71	230	97	17	248
8:00	133	15		455	172	627	144	16	677
9:00	143	20		604	282	886	154	22	956
10:00	80	51		434	280	714	86	55	770
11:00	85	33		315	245	560	92	36	604
12:00	73	91		340	302	642	79	98	693
13:00	51	54		300	312	612	55	58	660
14:00	63	31		277	316	593	68	33	640
15:00	63	28		289	325	614	68	30	663
16:00	102	85		327	475	802	110	92	865
17:00	88	66		356	543	899	95	71	970
18:00	80	23		442	648	1090	86	25	1176
19:00	63	40		404	486	890	68	43	960
20:00	50	35		266	377	643	54	38	694
21:00	33	40		141	361	502	36	43	542
22:00	38	26		108	268	376	41	28	406
23:00	20	10		96	167	263	22	11	284
	1,325	670		5,473	5,880				

Seasonal Adjustment Factor = 1.079

### Appendix A: Cuyahoga County Engineer's Office Traffic Count

### **Broadview Road and Valley Parkway Drive Intersection**

	Traf	fic Volum	e Summai	y (12/04	(2009)		Adju	sted Vol	umes
Time	EB	WB	EB+WB	NB	SB	NB+SB	EB	WB	NB+SB
0:00	7	1		38	38	76	8	1	82
1:00	4	1		25	26	51	4	1	55
2:00	1	1		14	13	27	1	1	29
3:00	2	0		6	6	12	2	0	13
4:00	1	2		10	11	21	1	2	23
5:00	6	1		11	13	24	6	1	26
6:00	9	1		57	63	120	10	1	129
7:00	45	6		210	226	436	49	6	470
8:00	101	7		521	526	1047	109	8	1130
9:00	101	17		576	561	1137	109	18	1227
10:00	60	12		397	402	799	65	13	862
11:00	39	15		315	319	634	42	16	684
12:00	35	26		335	345	680	38	28	734
13:00	33	26		353	345	698	36	28	753
14:00	37	27		304	305	609	40	29	657
15:00	45	26		305	302	607	49	28	655
16:00	60	37		328	336	664	65	40	716
17:00	50	54		397	388	785	54	58	847
18:00	59	44		424	429	853	64	47	920
19:00	38	21		382	368	750	41	23	809
20:00	28	14		227	222	449	30	15	484
21:00	17	10		142	144	286	18	11	309
22:00	22	7		114	117	231	24	8	249
23:00	6	3		69	66	135	6	3	146
	806	359		5,560	5,571				

Seasonal Adjustment Factor = 1.079

## Appendix A: Cuyahoga County Engineer's Office Traffic Count

### **Broadview Road and Macintosh Lane/Hamilton Drive Intersection**

	Traffi	c Volume S	Summary (	11/17-12/	(03/2009)		Adj	usted Vo	lumes
Time	EB	WB	EB+WB	NB	SB	NB+SB	EB	WB	NB+SB
0:00	3	5		23	57	80	3	5	86
1:00	1	3		11	41	52	1	3	56
2:00	2	0		8	13	21	2	0	23
3:00	0	1		1	6	7	0	1	8
4:00	0	1		7	8	15	0	1	16
5:00	2	5		3	3	6	2	5	6
6:00	7	10		10	13	23	8	11	25
7:00	15	36		72	52	124	16	39	134
8:00	46	124		164	173	337	50	134	364
9:00	90	159		182	212	394	97	172	425
10:00	59	114		132	179	311	64	123	336
11:00	42	67		131	146	277	45	72	299
12:00	26	49		133	167	300	28	53	324
13:00	33	44		127	208	335	36	47	361
14:00	37	46		127	216	343	40	50	370
15:00	24	32		167	189	356	26	35	384
16:00	40	61		163	277	440	43	66	475
17:00	36	62		213	321	534	39	67	576
18:00	28	61		283	327	610	30	66	658
19:00	36	76		204	323	527	39	82	569
20:00	25	81		124	215	339	27	87	366
21:00	13	38		77	163	240	14	41	259
22:00	8	37		79	117	196	9	40	211
23:00	6	5		47	59	106	6	5	114
	579	1,117		2,488	3,485				

Seasonal Adjustment Factor = 1.079

### Appendix A: Cuyahoga County Engineer's Office Traffic Count

#### **Broadview Road and Boston Road Intersection**


	Traf	ffic Volum	ne Summa	ry (12/02	(/2009)		Adjusted Volumes				
Time	EB	WB	EB+WB	NB	SB	NB+SB	EB	WB	NB+SB		
0:00	1	9		30	14	44	1	10	47		
1:00	2	2		11	14	25	2	2	27		
2:00	1	2		7	5	12	1	2	13		
3:00	0	1		2	3	5	0	1	5		
4:00	3	0		7	6	13	3	0	14		
5:00	4	3		0	6	6	4	3	6		
6:00	13	10		8	22	30	14	11	32		
7:00	57	50		54	70	124	62	54	134		
8:00	111	82		117	211	328	120	88	354		
9:00	126	62		122	207	329	136	67	355		
10:00	63	36		106	142	248	68	39	268		
11:00	31	44		110	106	216	33	47	233		
12:00	28	47		100	146	246	30	51	265		
13:00	34	34		110	138	248	37	37	268		
14:00	38	48		113	129	242	41	52	261		
15:00	23	56		153	153	306	25	60	330		
16:00	44	71		151	186	337	47	77	364		
17:00	46	116		199	216	415	50	125	448		
18:00	54	133		277	201	478	58	144	516		
19:00	47	72		200	173	373	51	78	402		
20:00	38	27		119	122	241	41	29	260		
21:00	26	22		83	92	175	28	24	189		
22:00	12	18		83	59	142	13	19	153		
23:00	10	16		40	40	80	11	17	86		
	812	961		2,202	2,461						

Seasonal Adjustment Factor = 1.079

### **West Wallings Road and Briarwood Drive Intersection**

				Warı	ants	Summ	arv						
Information							y						
Analyst Agency/Co Date Performed Project ID East/West Street File Name	4, W	OACA /13/20 /. Wall	10 ings	Road rwood_8	9 vhv	Intersection  Jurisdiction Units Uni						eights ary 09	arwood
Project Description													
General					sonor:		***	Roa	dway I	Networ	k		
Major Street Speed (mph)	35	П	_	opulation				Two	Major	Route	s		
Nearest Signal (ft)	4380		ГС	Coordinate	ed Sign	al Syste	em	We	ekend	Count			
Crashes (per year)	1	П	Ī A	Adequate	Trials o	f Altern	atives	5-yr	Grow	th Facto	or		0
Geometry and Traffic			El	В	T	WB			NB			SB	
-		LT	Th	H RT	LT	TH	RT	LT	TH	RT	LT	TH	RT
Number of lanes, N		0	1	0	0	1	0	0	0	0	0	1	0
Lane usage			L	T	-	TR					<u> </u>	LTR	
Vehicle Volume Averag (vph)	es	0	36	0 0	0	374	0	0	0	0	0	26	0
Peds (ped/h) / Gaps (gaps/h)			/			/			1			1	
Delay (s/veh) / (veh-hr)			/			/			/			/	
	Warrant 1: Eight-Hour Vehicular Volume												
1 A. Minimum Vehicular													
1 B. Interruption of Conf												_	
1 80% Vehicularand	and the Contract of the Contra				th majo	r appro	aches	and	higher	minor	approa	ich)	
Warrant 2: Four-Hour							22	w(100.5)				$\rightarrow$	
2 A. Four-Hour Vehicula	ar Voli	umes	Both	major ap	proach	esand	d highe	er min	or appi	roach)			
Warrant 3: Peak Hour												$\rightarrow$	
3 A. Peak-Hour Condition	_												
3 B. Peak- Hour Vehicu			(Bot	th major a	pproac	hesar	nd high	ner mi	nor app	oroach)			
Warrant 4: Pedestrian													
4 A. Pedestrian Volume		-				nd							
4 B. Gaps Same Period	(Fou	r hours	or	one ho	ur)	100							
Warrant 5: School Cro		7											
5. Student Volumesar	nd												
5. Gaps Same Period													
Warrant 6: Coordinate	d Sig	nal Sy	sten	n									Till I
6. Degree of Platooning	(Pred	domina	ınt di	rection or	both d	irections	s)						
Warrant 7: Crash Expe	erienc	e					2010						П
7 A. Adequate trials of a	lterna	itives,	obse	rvance a	nd enfo	rcemen	t failed -	-and-					
7 B. Reported crashes s	usce	ptible t	o cor	rrection b	y signa	l (12-mc	onth peri	iod)	and				


#### **West Wallings Road and Briarwood Drive Intersection**



### East Royalton Road & Cherry Hill Lane/Ledgemont Drive Intersection

			Warra	ants	Summ	arv	-					
Information				1		,						
Date Performed 4/2 Project ID East/West Street Ro	DACA 2/2010 byalton	Ledgem	ont_8_	8.xhy	Jurisdiction Ledgem Jurisdiction Broadvie Units U.S. Cu Time Period Analyzed Novemb					iew Heights ustomary ber 2009 nont Dr./Cherry Hill		
Project Description												
General							Roa	dway N	letwor	k		
Major Street Speed (mph) 35	Г	Pop	ulation	< 10,0	000		Tw	o Major	Route	s		
Nearest Signal (ft) 930		Coo	rdinate	d Sign	al Syste	em	We	ekend	Count			
Crashes (per year) 3	П	Ade	quate 7	Trials c	of Altern	atives	5-у	r Growt	h Facto	or		0
											SB	
	LT	TH	RT	LT	TH	RT	LT	TH	RT	LT	TH	RT
Number of lanes, N	1	1	0	1	1	0	0	1	0	0	1	0
Lane usage	L	TR		L	TR			LTR		_	LTR	
Vehicle Volume Averages (vph)	7	710	0	5	707	0	0	19	0	0	23	0
Peds (ped/h) / Gaps (gaps/h)		1			/			/			/	
Delay (s/veh) / (veh-hr)		1			/	1		/			/	
Warrant 1: Eight-Hour Veh	-											
1 A. Minimum Vehicular Volu		- Mariana -										П
1 B. Interruption of Continuo							_					
1 80% Vehicularand Inte			es (Bot	h majo	r appro	aches	-and	higher	minor	approa	ch)	
Warrant 2: Four-Hour Vehi												
2 A. Four-Hour Vehicular Vo	lumes	(Both m	ajor apı	proach	iesand	d highe	er min	or appr	oach)			
Warrant 3: Peak Hour												
3 A. Peak-Hour Conditions (				an-Lin								
3 B. Peak- Hour Vehicular V		(Both n	najor ap	oproac	nesar	na nigr	ner mi	nor app	proach)			
Warrant 4: Pedestrian Volumes (Fa				\ -							_	
4 A. Pedestrian Volumes (Fo				,	na						$\dashv$	
Warrant 5: School Crossin		501 0	nie nou									
5. Student Volumesand	y										$\dashv$	
5. Gaps Same Period		-										
Warrant 6: Coordinated Sig	inal Si	/stem									_	, III
6. Degree of Platooning (Pre			tion or	both d	irections	s)						
Warrant 7: Crash Experien			+					**=				
7 A. Adequate trials of altern		observa	ince an	d enfo	rcemen	t failed -	-and-	_				
7 B. Reported crashes susce					74					-		


### East Royalton Road & Cherry Hill Lane/Ledgemont Drive Intersection



### **Broadview Road and Akins Road/Faulhaber Road Intersection**

				Warra	ants	Summ	ary						
Information	-								WELL				
Analyst Agency/Co Date Performed Project ID	N 4,	T IOAC <i>A</i> /13/20	10	S2 - 22 - 22		Intersection Broadview Rd. and Rd. Jurisdiction Broadview Heights U.S. Customary							Akins
East/West Street File Name	D	rivewa	load/Cit ay iewAkin			Time Period Analyzed North/South Street Major Street Broadview Heights North-South							
Project Description					7								
General			Roa	dway N	letwor	k							
Major Street Speed (mph)	mph) 35 -					000		Tw	o Major	Route			F
Nearest Signal (ft)	500					al Syste			ekend				
Crashes (per year)	2		Ade	quate 1	rials o	f Altern	atives	5-у	r Growt	h Facto	or		0
Geometry and Traffic			EB	T ==		WB			NB		_	SB	
	-	LT	TH	RT	LT	TH	RT	LT	TH	RT	LT	TH	RT
Number of lanes, N Lane usage	_	0	1 LTR	0	1 L	1 TR	0	0	1 LTR	0	0	1	0
Vehicle Volume Average (vph)	s	0	92	0	0	48	0	0	408	0	0	1397	0
Peds (ped/h) / Gaps (gaps/h)			1			1			/			/	
Delay (s/veh) / (veh-hr)			/		/ / / / / / /								
Warrant 1: Eight-Hour	Vehi	cular	Volume	1									
1 A. Minimum Vehicular	Volu	mes (f	3oth ma	jor appı	roache	sand	highe	r mino	or appro	ach) -	-or		
1 B. Interruption of Conti	nuou	ıs Traf	fic (Both	n major	appro	aches -	and hi	igher	minor a	pproac	h)or		
1 80% Vehicularand	Inter	ruptior	1 Volum	es (Bot	h majo	r appro	aches	and	higher	minor	approa	ıch)	
Warrant 2: Four-Hour V	ehic	cular \	/olume										
2 A. Four-Hour Vehicular	Vol	umes	(Both m	ajor app	oroach	esan	d highe	er mir	or appr	roach)			
Warrant 3: Peak Hour	11.7518												П
3 A. Peak-Hour Condition	ns (N	linor o	lelaya	nd mi	nor vo	lumea	and tot	al vol	ume )	-or			
3 B. Peak- Hour Vehicula	ar Vo	lumes	(Both r	najor ap	oproac	hesa	nd high	ner mi	nor app	oroach)			
Warrant 4: Pedestrian \	/olu	me										$\neg \neg$	
4 A. Pedestrian Volumes	(Fo	ur hou	rsor	one ho	ur)a	nd							
4 B. Gaps Same Period (	(Fou	r hours	sor c	ne hou	r)								
Warrant 5: School Cros	sing	7										$\neg \neg$	
5. Student Volumesand	b												
5. Gaps Same Period				•									100
Warrant 6: Coordinated	l Sig	nal Sy	/stem									Ť	F
6. Degree of Platooning (	Prec	domina	ant direc	tion or	both d	irection	s)			74642			
Warrant 7: Crash Exper	rienc	e										T	
7 A. Adequate trials of all	terna	itives,	observa	ance an	d enfo	rcemen	t failed -	-and-	-				
7 B. Reported crashes su	ısceı	otible 1	o correc	ction by	signa	(12-mc	onth per	iod)	and				


#### **Broadview Road and Akins Road/Faulhaber Road Intersection**



### **Broadview Road and Valley Parkway Drive Intersection**

				Warr	ants	Summ	arv						
Information				vvaii		- Curring	ui y				- MI-TH		
Date Performed 4/Project ID East/West Street Value	OAC 13/20 alley	10 Parkw		kway8_	8.xhy	Intersection  Jurisdiction Units Time Period Analyzed North/South Street  Intersection Broadview Rd & Vanch							ley
Project Description													
General Roadway Network  Major Street Speed of Population < 10,000 Two Major Poutos													
Major Street Speed (mph)	ph)								o Major	Route	s		
Nearest Signal (ft)	2200		-			al Syste	30000	We	ekend	Count			
Crashes (per year)	3		Ade	equate 7	Trials o	of Altern	atives	5-у	r Growt	h Facto	or		0
Geometry and Traffic			EB	T ==		WB			NB			SB	
Number of lanes, N	$\dashv$	LT	TH	RT	LT	TH	RT	LT	TH	RT	LT	TH	RT
Lane usage	$\dashv$	0	1 LTR	0	0	1 LTR	0	0	1 LTR	0	0	1 LTR	0
Vehicle Volume Average	s	22											-
(vph)		0	59	0	0	28	0	0	416	0	0	416	0
Peds (ped/h) / Gaps (gaps/h)			1			/			/			1	
Delay (s/veh) / (veh-hr)			/			1			/			1	
Warrant 1: Eight-Hour						14111							П
1 A. Minimum Vehicular				-									
1 B. Interruption of Conti	-							_					
1 80% Vehicularand	100				h majo	or appro	aches -	-and	higher	minor a	approa	ch)	
Warrant 2: Four-Hour V													
2 A. Four-Hour Vehicular	r Volu	ımes	(Both m	ajor ap	proach	nesand	d high	er min	or appr	oach)			
Warrant 3: Peak Hour												_	
3 A. Peak-Hour Condition						- 27						_	
3 B. Peak- Hour Vehicula	-	-	(Both I	najor aj	oproac	nesar	ıa nıgı	ner mi	nor app	proach)			
Warrant 4: Pedestrian \												$\rightarrow$	_
4 A. Pedestrian Volumes 4 B. Gaps Same Period (	•		-			na						$\rightarrow$	
Warrant 5: School Cros			501 1	one nou								_	
5. Student Volumesand												$\dashv$	E
5. Gaps Same Period												$\neg$	F
Warrant 6: Coordinated	Sig	nal Sy	stem										
6. Degree of Platooning (	(Pred	lomina	ant dire	ction or	both d	irections	s)	90					
Warrant 7: Crash Exper	rienc	e		4								T	
7 A. Adequate trials of all	terna	tives,	observ	ance an	d enfo	rcemen	t failed	and-	-				
7 B. Reported crashes su	ıscep	otible t	o corre	ction by	signa	l (12-mc	nth per	iod)	and				


### **Broadview Road and Valley Parkway Drive Intersection**



### **Broadview Road and Macintosh Lane/Hamilton Drive Intersection**

				Warr	ants :	Summ	arv						
Information			2 1000-1000										
Analyst Agency/Co Date Performed Project ID	4/13	ACA 3/2010				Intersection  Jurisdiction Units  Broadview Rd. & M Ln. Broadview Heights U.S. Customary						eights	cintosh
East/West Street File Name	Driv	/e	ı Lane/l vMacint			Time Period Analyzed North/South Street Broadview Road Major Street North-South						ad	
Project Description								tin-					
General								Roa	dway I	Vetwor	k		
Major Street Speed (mph)	45		<del></del>	ulation				1		Route	s		П
Nearest Signal (ft)	4400					al Syste		_	ekend				
Crashes (per year)	2		Ade	quate	rials o	f Altern	atives	5-у	r Growt	th Facto	or		0
Geometry and Traffic			EB		l	WB			NB			SB	
		LT	TH	RT	LT	TH	RT	LT	TH	RT	LT	TH	RT
Number of lanes, N Lane usage	_	0	1 LTR	0	0	1 LT	1 R	0	1 LTR	0	0	1 LTR	0
Vehicle Volume Average	es	V2.00											
(vph) Peds (ped/h) / Gaps		0	44	0	0	80	0	0	182	0	0	246	0
(gaps/h)			/			/			/			/	
Delay (s/veh) / (veh-hr)			/			/			/			/	
Warrant 1: Eight-Hour	Vehi	cular	Volume										
1 A. Minimum Vehicular	_			-		-		_					
1 B. Interruption of Conf	inuou	s Traf	fic (Both	n major	appro	aches -	and h	igher	minor a	pproac	h)or		
1 80% Vehicularand		-		es (Bot	h majo	r appro	aches -	-and	higher	minor	approa	ıch)	
Warrant 2: Four-Hour		CONTRACTOR NO				-10722							
2 A. Four-Hour Vehicula	ır Volu	umes (	Both m	ajor ap	oroach	esan	d high	er min	or appi	roach)			
Warrant 3: Peak Hour													
3 A. Peak-Hour Condition													
3 B. Peak- Hour Vehicu	lar Vo	lumes	(Both n	najor a	oproac	hesa	nd high	her mi	nor app	oroach)			
Warrant 4: Pedestrian			W450.	alley-									
4 A. Pedestrian Volume	s (Fo	ur houi	rsor	one ho	ur)a	nd							
4 B. Gaps Same Period	(Fou	r hours	or c	ne hou	ır)								
Warrant 5: School Cro	ssing	1											
5. Student Volumesar	nd				-080						7.0		
5. Gaps Same Period													
Warrant 6: Coordinate	d Sig	nal Sy	stem										
6. Degree of Platooning	(Prec	domina	int direc	tion or	both d	irection	s)						
Warrant 7: Crash Expe													
7 A. Adequate trials of a													
7 B. Reported crashes s	usce	otible t	o correc	tion by	signa	l (12-ma	onth per	iod)	and				

#### **Broadview Road and Macintosh Lane/Hamilton Drive Intersection**



#### **Broadview Road and Boston Road Intersection**

					Morr	onto	Cumm							
Information					warra	ants	Summ	lary						
Analyst Agency/Co Date Performed Project ID East/West Street File Name	N 4	T IOACA /13/20 oston roadv	10 Ro		on8_8.>	vhv	Intersection  Jurisdiction Units Time Period Analyzed North/South Street Major Street  Broadview Rd. & B Rd. Broadview Heights U.S. Customary December 2009 Broadview Road North-South						eights ary 09	ston
Project Description							:							
General							Roadway Network							
Major Street Speed (mph)	45	Г	0	Pop	ulation	< 10,0	7,000 Two Major Routes							
Nearest Signal (ft)	5800	Г		Coo	rdinate	d Sign	al Syste	em	We	ekend (	Count			
Crashes (per year)	7		B	Ade	quate 1	Trials o	f Altern	atives	5-у	r Growt	h Facto	or		0
Geometry and Traffic			E				WB			NB			SB	
	_	LT	_	TH	RT	LT	TH	RT	LT	TH	RT	LT	TH	RT
Number of lanes, N		0	_	1	0	0	1	0	0	1	0	0	1	0
Lane usage	$\dashv$			LTR			LTR			LTR			LTR	
Vehicle Volume Average (vph)	es	0		58	0	0	72	0	0	158	0	0	180	0
Peds (ped/h) / Gaps (gaps/h)			/				/		1	1			1	
Delay (s/veh) / (veh-hr)			_	1			/			1			1	
Warrant 1: Eight-Hour														F
1 A. Minimum Vehicular	Volu	mes (l	3ot	h ma	jor app	roache	sand	highe	r mino	r appro	ach)	or		
1 B. Interruption of Cont	inuou	is Traf	fic	(Both	n major	appro	aches	and h	igher ı	minor a	pproac	h)or		
1 80% Vehicularand	Inter	ruption	١V	olum	es (Bot	h majo	r appro	aches -	-and	higher	minor a	approa	ch)	100
Warrant 2: Four-Hour	Vehic	cular \	/ol	ume										
2 A. Four-Hour Vehicula	r Vol	umes	(Bo	th m	ajor apı	proach	esand	d high	er min	or appr	oach)			
Warrant 3: Peak Hour														
3 A. Peak-Hour Condition			_	_										
3 B. Peak- Hour Vehicul	ar Vo	lumes	(B	oth n	najor a	oproac	hesar	nd hig	her mi	nor app	roach)			
Warrant 4: Pedestrian	Volu	me												
4 A. Pedestrian Volumes				_			nd							Till 1
4 B. Gaps Same Period	(Fou	r hour	3	or c	ne hou	ır)								
Warrant 5: School Cro	ssing	7												
5. Student Volumesan	d													
5. Gaps Same Period														
Warrant 6: Coordinate	d Sig	nal S	/st	em										
6. Degree of Platooning	(Pred	domina	ant	direc	tion or	both d	irections	s)						
Warrant 7: Crash Expe	riend	e			No.									
7 A. Adequate trials of a			_	-										
7 B. Reported crashes s	usce	ptible	to c	correc	ction by	signa	l (12-mc	onth per	iod)	and				~

#### **Broadview Road and Boston Road Intersection**

